

Model:

YXP1500RSC

Enclosed set

Open set



Frequency	Phases	Power Factor	Prime Output	Standby Output
50Hz	3	0.8	1500 kVA / 1200 kW	1650 kVA / 1320 kW

Ratings

- Prime output: This rating is applicable for supplying continuous electrical power at variable load. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.
- Standby output: This rating is applicable for supplying electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings.
- Standard reference conditions: 25°C, 100m A.S.L., 30% relative humidity

Design features

- High quality assembly, providing stiffness and low vibration
- Power coated steel. Corrosion and scratch resistant.
- Compact and long service life
- Wiring and connectors with double protection.
- Protection guards in radiator and high voltage parts.
- Full 12 month YorPower warranty

Design Standards

- CE marking
- ISO8528-1995
- GB/T2820-1997
- ISO 9001:2015 Registered Company

Configuration

- 4-Stroke water-cooled diesel engine.
- Industrial silencer.
- Coolant recovery tank
- Single bearing, 4 pole brushless alternator.
- Anti vibration mountings
- Integral fuel tank with fully bunded base protection.
- Fuel level sensor
- Auto start control system with electronic digital control module DSE7420
- Output circuit breaker.
- Emergency stop button
- High engine temperature and low oil pressure shutdown system.
- 24V starter battery with leads and switch

Acoustic canopy features

- Water and dust proof design
- Door locks
- High quality sound absorbing and fire retardant inner material
- Lifting lugs
- Forklift holes in base (open set only)

** The images above are for illustration purposes only.

Engine data



Engine brand	Perkins	Total coolant capacity	207 Litres
Engine model	4012-46TAG2A	Total lube oil capacity	177 Litres
Engine speed	1500 RPM	Cooling air flow	TBC
Number of cylinders	12	Exhaust gas flow	TBC
Aspiration	Turbocharged & Aftercooled	Exhaust gas temperature	TBC
Combustion system	Direct injection	Fuel cons. @ 110% standby load	341 l/hr
Displacement	45.842 Litres	Fuel cons. @ 100% Prime load	310 l/hr
Governor type	Electronic	Fuel cons. @ 75% Prime load	234 l/hr
Cooling system	Water Cooled	Fuel cons. @ 50% Prime load	157 l/hr

Alternator data

Alternator brand	Leroy Somer	Number of wires	6
Alternator model	LSA50.2L8	AVR model	R 450
Excitation	AREP or PMG	Voltage regulation	± 0.5%
Insulation class	H	Total Harmonic distortion	< 3.5%
Drip proof protection	IP23	Telephone interference	TIF < 50%, FHT < 2%
Winding pitch	2/3 (N° 6S)	Flanges and shield	Cast Iron

Enclosed set data

Open set data



L x W x H (mm)	Weight	Fuel tank	Noise@7M
12192 x 2438 x 3159	19469 kg	2000 Litres	76db

L x W x H (mm)	Weight	Fuel tank	Noise@7M
4680 x 1800 x 2385	9403 kg	N/A	118db

** Due to constant innovation, design and specifications are subject to change without notice, All YorPower Products are supplied from the UK.