

Genset  
Model:

## YTP275RS & YTP275RSC

T-Series

Enclosed set



Frequency	Phase	Power Factor	Prime Output	Standby
50Hz	3	0.8	250kVA / 200kW	275kVA / 220kW

### Ratings

- Prime output: This rating is applicable for supplying continuous electrical power at variable load. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.
- Standby output: This rating is applicable for supplying electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings.
- Standard reference conditions: 25°C, 100m A.S.L. 30% relative humidit

### Design Features

- High quality assembly, providing stiffness and low vibration
- Powder coated steel, treated with anti corrosion paint
- Compact and easy access for service
- Wiring and connectors with protection
- All moving parts protected with guards
- Synchronised upgrade options available
- Governor type: electronic / mechanical
- Battery charger and block heater options
- BMS output signaling included

### Configuration

- 4-Stroke water-cooled diesel engine.
- Industrial / residential silencer
- Coolant recovery tank
- Single bearing, 4 pole brushless alternator
- Anti vibration mountings
- Integral fuel tank (with bunded base option)
- Fuel level gauge
- Auto start control system with electronic digital control module DSE7320
- ABB output circuit breaker.
- Emergency stop button
- High engine temperature and low oil pressure shutdown system.
- 12V / 24V starter battery with leads and isolator switch

### Acoustic canopy features

- Weather proof enclosure
- Fully lockable doors and control panel
- High quality sound absorbing material
- Lifting lugs

Unit 2, Hurricane Close, Sherburn in Elmet, Leeds, LS25 6PB, United Kingdom  
+44 1977 688155 • sales@yorpower.com

[www.yorpower.com](http://www.yorpower.com)


## Engine data

Engine brand	Perkins	Total coolant capacity	25 Litres
Engine model	1206A-E70TTAG3	Total lube oil capacity	16 Litres
Engine speed	1500 RPM	Cooling air flow	265.2 m <sup>3</sup> /min
Cylinders	6	Exhaust gas flow	33.7 m <sup>3</sup> /min
Aspiration	Turbo Charge	Exhaust gas temperature	511°C
Combustion system	Direct injection	Fuel cons. @ 110% standby load	64.5 l/hr
Displacement	7.01 Litres	Fuel cons. @ 100% Prime load	56.9 l/hr
Governor type	Electronic	Fuel cons. @ 75% Prime load	41.5 l/hr
Cooling System	Water	Fuel cons. @ 50% Prime load	28.1 l/hr

## Alternator data


Alternator brand	Leroy Somer	Number of wires	6
Alternator model	TAL046E	Efficiency	93.3%
Excitation	AVR, Brushless	Voltage regulation	± 5%
Insulation class	H	Total Harmonic distortion	< 5% no load
Drip proof protection	IP23	AVR	Brushless
Connection type	YILDIZ	Power factor	0.8

## Enclosed set data



W x L x H (mm)	Weight	Fuel tank	Noise@7M
1200 x 3860 x 1850	2452 kg	330 Litres	71 db

## Open set data



\*\* The images are for illustration purposes only.

W x L x H (mm)	Weight	Fuel tank	Noise@7M
1200 x 2700 x 1730	19011 kg	330 Litres	N/A

Unit 2, Hurricane Close, Sherburn in Elmet, Leeds, LS25 6PB, United Kingdom  
+44 1977 688155 • sales@yorpowers.com

[www.yorpowers.com](http://www.yorpowers.com)